

# CeramSource Inc. Ceramic Fiber Blankets

## Safety Data Sheet

### 1. PRODUCT NAME

**Trade Name:** TaoFibre® Blanket

**Product Name:** Aluminosilicate Fiber Blankets

**Material Name:** Ceramic Fiber, Aluminosilicate Refractory Fiber, Refractory Ceramic Fiber (RCF)

**General Use:** High temperature insulation

**Product Series:** Blankets: COM Type, STD Type, HP Type, HA Type

Manufactured and supplied by:

Ceramsource Inc.

P.O. Box 6026

26-B Kennedy Blvd

East Brunswick, NJ 08816

Tel: 732-257-5002 Fax: 732-257-5003

### 2. HAZARDS IDENTIFICATION

#### (a) Classification of the chemical in accordance with paragraph (d) of §1910.1200

The U.S. Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (HCS) 2012 indicates that IARC Group 2B corresponds to OSHA HCS 2012 Category 2 carcinogen classification (see, e.g., §1910.1200, Appendix F, Part D).

#### (b) Signal word, hazard statement(s), symbol(s) and precautionary statement(s) in accordance with paragraph (f) of §1910.1200

Under OSHA HCS 2012, RCF is classified as a category 2 carcinogen.

**Hazard Pictogram**



**Signal Word**

Warning

**Hazard Statements**

Suspected of causing cancer by inhalation.

**Precautionary statements**

Do not handle until all safety instructions have been read and understood.  
Use respiratory protection as required; see section 8 of the Safety Data Sheet.  
If concerned about exposure, get medical advice.  
Store in a manner to minimize airborne dust.  
Dispose of waste in accordance with local, state and federal regulations.

**Supplementary Information**

May cause temporary mechanical irritation to exposed eyes, skin or respiratory tract.  
Minimize exposure to airborne dust.

**3. COMPOSITION AND INGREDIENTS**

<u>Ingredient Name</u>	<u>CAS Number</u>	<u>Percent</u>
Aluminosilicate fiber	142844-00-6	100

**4. FIRST AID**

**Eye contact:** Flush immediately with large amounts of water for at least 15 minutes. Do not rub eyes. Get medical help if irritation persists.

**Skin contact:** Do not rub or scratch affected skin. Wash affected area gently with soap and water. Skin cream or lotion can also help after washing.

**Ingestion:** Relocate affected individual to an environment of clean and fresh air. Drink plenty of water. Seek medical help if symptoms persist.

**Inhalation:** Remove affected individual to a dust free place. Seek medical help if irritation persists.

**Notes to Physicians:** Skin and respiratory effects are the result of mechanical irritation; fiber exposure does not result in allergic manifestations.

**5. FIRE FIGHTING MEASURES**

**NFPA Unusual Hazards:** None

**Flash Point:** None.

**Auto-ignition Temperature:** None.

**Extinguishing Media:** Use proper extinguishing media for the surrounding fire.

**Unusual Fire and Explosion Hazards:** None.

**Fire Fighting Protective Equipment:** Wear full bunker gear including positive pressure self-contained breathing apparatus.

## 6. ACCIDENTAL RELEASE MEASURES

Avoid creating airborne dust. Maintain routine housecleaning procedures. Vacuum only with HEPA filtered equipment. If sweeping is necessary, use a dust suppressant and keep material in closed containers. Do not use compressed air for clean-up. Workers should wear gloves, goggles and approved respirator. Avoid clean-up procedures that could cause water pollution.

## 7. HANDLING AND STORAGE

**Handling:** Minimize use of power tools to handle the material. Use hand tools whenever possible. Frequently clean work area with HEPA filtered vacuum or wet sweeping to minimize the accumulation of debris. Do not use compressed air for clean-up.

**Storage:** Store the material in factory container in a dry area. Keep container closed when not in use.

**Empty Containers:** Product packaging may contain residue. Do not reuse.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines:

<u>Components</u>	<u>OSHA (PEL)</u>	<u>ACGIH (TLV)</u>	<u>Supplier</u>
Alumino-silicate fiber (vitreous) TWA (RCFC)*	Non-established	0.2 f/cc	0.5 fiber/cc 8-hr

\*Pending the results of long-term health effects studies, airborne exposures should be controlled at or below the Refractory Ceramic Fiber Coalition (RCFC) Recommended Exposure Guidelines listed above.

### Other Occupational Exposure Levels (OEL):

RCF-related occupational exposure limits vary from country to country. Listed here are a few regulatory OEL examples: Australia – 0.5 f/cc; Austria – 0.5 f/cc; Canada – 0.5 to 1 f/cc; Denmark – 1 f/cc; France – 0.6 f/cc; Germany – 0.5 f/cc; Netherlands – 1 f/cc; New Zealand – 1 f/cc; Norway – 2 f/cc; Poland – 2 f/cc; Sweden – 1 f/cc; United Kingdom – 2 f/cc. Non-regulatory OEL

example is: RCFC REG 0.5 f/cc. The objectives and criteria underlying each of these OEL decisions also vary. The evaluation of occupational exposure limits and determining their relative applicability to the workplace is best performed, on a case-by-case basis, by a qualified industrial hygienist.

**Engineering controls:** Use engineering controls such as ventilation and dust collection devices to limit airborne fiber concentrations to the minimum attainable level.

**Protective clothing:** Workers should wear full body clothing, gloves, hat and eye protection when handling the material. Wash work clothes separately from normal clothing. Rinse washer after use. It is recommended workers do not take work clothing out of the work area. If they must, they should vacuum their clothes with a HEPA filtered vacuum before leaving the work area.

**Eye protection:** Wear goggles / safety glasses with side-shields.

**Respiratory protection:** Other than or before availability of engineering controls to reduce airborne aluminosilicate dust below the PEL, workers should use good work practices together with respiratory protection. Before providing respirators to workers, employers should 1) monitor for airborne aluminosilicate dust concentrations using proper NIOSH analytical methods and select the respiratory protection according to the results of that monitoring, 2) have physician determine if the workers are able to wear respirators, 3) make training programs available to workers for respiratory protection. Use NIOSH/MSHA approved respirators, in accordance with OSHA Respiratory Protection Standard 29 CFR 1910.134 and 29 DFR 1926.103, for the particular hazard or airborne concentrations in the work place.

**Recommended Respiratory Protections (When Handling Aluminosilicate Fiber Products):**

<u>Dust Concentration</u>	<u>Recommended Respirator</u>
Less than 0.5 f/cc	No specific recommendation. Use preference based upon conditions present.
0.5 f/cc to 5.0 f/cc	Disposable dust/mist respirator (e.g. 3M 9900) or half-face, air-purifying respirator equipped with high efficiency particulate air (HEPA) filter cartridges (e.g. 3M 6000 Series)
5.0 f/cc to 25 f/cc	Full-face air-purifying respirator equipped with high-efficiency particulate air (HEPA) filter cartridges (e.g. 3M 7800 with 7255 filters) or powered with air-purifying respirator (PARR) equipped with HEPA filter cartridges (e.g. 3M W3265S with W3267 filters)
More than 25 f/cc	Full-face positive pressure supplied air respirator (e.g. 3M7800 with W9435 hose and W3196 regulator)

**Other Information:**

- (1) Concentrations based upon an eight hour time weighted average (TWA) as determined by air samples collected and analyzed pursuant to NIOSH method 7400 (B) for airborne fibers.
- (2) During furnace tear-out activities/after service RCF removals, the manufacturer recommends, at a minimum, the use of full-face-piece air purifying respirator equipped with a high-efficiency particulate air (HEPA) filter cartridge to control fiber and potential crystalline silicate exposure.
- (3) In the absence of other objective data or when concentrations are unknown, the manufacturer recommends the use of half-face, air purifying respirator equipped with a high-efficiency particulate air (HEPA) filter cartridge.
- (4) Situations involving a potential exposure to airborne contaminants should be evaluated by a qualified industrial hygienist for the selection of appropriate respiratory protection and air monitoring.
- (5) The American Conference of Governmental Industrial Hygienists (ACGIH) has not adopted a threshold limit value (TLV) recommendation for RCF.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** White and odorless.

**Chemical family:** Aluminosilicate fibers.

**Chemical Indexes:** Al<sub>2</sub>O<sub>3</sub>+SiO<sub>2</sub>: >97%

**Vapor pressure:** Not applicable

**Vapor density:** Not applicable

**Specific gravity range:** 2-2.7

Al<sub>2</sub>O<sub>3</sub>: >46%  
Fe<sub>2</sub>O<sub>3</sub>: <1.0%  
Na<sub>2</sub>O+K<sub>2</sub>O: <=0.5

**Melting point:** 3200 °F

**% Volatile:** Not applicable  
**Water solubility (%):** Not applicable  
**PH:** Not applicable  
**Boiling point:** Not applicable.

## **10. STABILITY AND REACTIVITY**

**Chemical stability:** Stable under conditions of normal use.

**Incompatibility:** Hydrofluoric acid, phosphoric acid, and concentrated alkali.

**Hazardous decomposition products:** None.

**Hazardous polymerization:** Not applicable.

## **11. TOXICOLOGICAL INFORMATION**

Epidemiological studies conducted by Institution of Human Environment Protection in China has provided no evidence that there is a direct cause-and-effect relationship between cumulative exposure to aluminosilicate fibers and lung cancers or particular pulmonary diseases.

However, recent toxicological experiments using physiological exposure method (inhalation) have produced findings of respiratory disease in rodents. Aluminosilicate refractory fiber has found to be a rodent carcinogen under the conditions that the rodents are exposed to high levels of the material (75 – 115 fibers/cc) on a basis of lifetime duration.

## **12. ECOLOGICAL INFORMATION**

No data is available on adverse effects of the material on the environment.

## **13. DISPOSAL CONCERNS**

This material is not classified as a hazardous waste under Federal regulations (40 CFR 261). It is the product users' responsibility to comply with local, regional, state or provincial regulations concerning specific requirements for disposal. Any processing, alteration or chemical additions to the material, as purchased, may make the information provided in this SDS incomplete, inaccurate, or inappropriate. Original product boxes may contain material residue. Do not reuse them for other packaging purposes.

## **14. TRANSPORT CONSIDERATIONS**

**U.S. Department of Transportation (DOT)**

**Bill of lading description:** Ceramic fiber textiles (49 CFR 172.202)

**Hazard class:** Not classified

**Labels:** Not applicable

**Placards:** Not applicable

**United Nations (UN) Number:** Not applicable

**North America (NA) Number:** Not applicable

## **15. REGULATORY INFORMATION**

**CERCLA:** The aluminosilicate fibers of this product have an average diameter of 2-4  $\mu\text{m}$  and are not considered CERCLA hazardous substances (CERCLA 40 CFR 302).

**Clean Air Act (CAA):** Substances regulated as hazardous air pollution under Section 112 of the Clean Air Act Amendments of 1990:

Chemical Name

None

Most RCF products, including aluminosilicate fibers, are composed of RCF with an average diameter greater than 1 micron, and therefore are not considered hazardous air pollutants.

**SARA Title III:** This material does not contain substances reportable under Section 302, 304, 313 (40 CFR 372). Section 311 and 312 apply.

**TSCA:** All substances contained in this product are listed in the TSCA Chemical Inventory (Section 8b).

### **State Regulations**

#### **California:**

Substances listed by the State of California on Proposition 65, the Safe Drinking Water and Toxic

Enforcement Act of 1986:

Chemical Name

Ceramic fibers (airborne particles of respirable size)

CAS Number

142844-00-6

#### **New Jersey:**

Chemicals which are listed as a special health hazard substances as defined in New Jersey Worker and Community Right to Know Act, New Jersey Administrative Code, Title 8, Department of Health, Chapter 59, Subchapter 10:

Chemical Name

NONE

CAS Number

#### **Pennsylvania:**

Chemicals which are listed as a special health hazard substance as defined in Pennsylvania Right-to-Know Law, Section 3800:

Chemical Name

NONE

CAS Number

### **International Regulations:**

**Canadian Workplace Hazardous Material Information System (WHMIS)** categories apply to this material as follows:

Acutely Toxic: --	Biohazardous: --	Compressed Gas: --
Corrosive: --	Dangerously Reactive: --	Flammable/Combustible: --
Oxidizer: --	Other Toxic Effects: X	

**Canadian Environment Protection Act (CEPA):**

All substances in this product are listed, as required, on the Domestic Substances List (DSL). Chemicals which are listed on the Non-Domestic Substances List:

<u>Chemical Name</u>	<u>CAS Number</u>
NONE	

## **16. OTHER INFORMATION**

**Removal after Service:** Under sustained and steady high temperature over 1800 °F, this material will possibly transform to crystalline silica (cristobalite) in exposed portions. Prolonged or repeated exposure to respirable crystalline silica dust may lead to lung diseases. IARC has listed crystalline silica in Category 2A, a probable carcinogen ("Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans." IARC Monograph 68, June 1997, p. 210-211). The permissible exposure limit (PEL) set by OSHA for respirable cristobalite is 0.05 mg/m<sup>3</sup>. Whenever possible, follow Section 8 procedures for exposure controls and personal protection.

**Abbreviations:**

CERCLA : Comprehensive Environmental Response Compensation and Liability Act of 1980

CAS: Chemical Abstracts Service

f/cc: Fibers per cubic centimeter  
HMIS: Hazardous Material Information System  
mg/m<sup>3</sup>: Milligrams per cubic meter of air  
NIOSH: National Institute for Occupational Safety and Health  
OSHA: Occupational Safety and Health Administration  
PEL: Permissible Exposure Limit  
SARA: Super Amendments and Reauthorization Act  
TSCA: Toxic Substances Control Act

---

The above information is collected and prepared with reasonable care. However, CeramSource, Inc. makes no warranty, expressed or implied, as to the accuracy or suitability of the data herein above. CeramSource Inc. assumes no responsibility for any damage or injury resulting from failure to follow the procedures recommended in this SDS of using, handling, and storing the material.